



Product #: RL-3118(6)



Product #: RL-3119(6)
Connex™ 6' Clear Pack Shock Absorbing Lanyard with 1 Locking Snap Hook, 1 #18 Locking Rebar Hook

Product Information:

- Length of Lanyard - 6'
- Rated Shock Pack Absorber Free Fall Limit - 6'
- Webbing Break Strength - 6,000 lbs.
- Connectors - Steel ANSI rated locking snap hook at attachment end and one steel ANSI rated rebar hook at anchorage end
- Meets OSHA and ANSI Z359.13-2009



Product #: RL-30198(6)
Connex™ 6' Twin Leg "Y" Style 100% Tie Off Clear Pack Shock Absorbing Lanyard with 3 Locking Snap Hooks

Product Information:

- Length of Lanyard - 6'
- Rated Shock Pack Absorber Free Fall Limit - 6'
- Webbing Break Strength - 6,000 lbs.
- Connectors - Steel ANSI rated locking snap hooks at all three ends
- Meets OSHA and ANSI Z359.13-2009



Product #: RL-30199(6)
Connex™ 6' Twin Leg "Y" Style 100% Tie Off Clear Pack Shock Absorbing Lanyard with 1 Locking Snap Hook, 2 #18 Locking Rebar Hooks

Product Information:

- Length of Lanyard - 6'
- Rated Shock Pack Absorber Free Fall Limit - 6'
- Webbing Break Strength - 6,000 lbs.
- Connectors - Steel ANSI rated locking snap hook at attachment end and two steel ANSI rated rebar hooks at anchorage ends
- Meets OSHA and ANSI Z359.13-2009



Product #: RL-3128(6)



Product #: RL-3129(6)
Connex™ 6' Internal Shock Absorbing Lanyard with 1 Locking Snap Hook, 1 #18 Locking Rebar Hook

- Product Information:**
- Length of Lanyard - 6'
 - Rated Shock Pack Absorber Free Fall Limit - 6'
 - Webbing Break Strength - 6,000 lbs.
 - Connectors - Steel ANSI rated locking snap hook at attachment end and one steel ANSI rated rebar hook at anchorage end
 - Meets OSHA and ANSI Z359.13-2009



Product #: RL-30298(6)
Connex™ 6' Twin Leg "Y" Style 100% Tie Off Internal Shock Absorbing Lanyard With 3 Locking Snap Hooks

- Product Information:**
- Length of Lanyard - 6'
 - Rated Internal Shock Absorber Free Fall Limit - 6'
 - Webbing Break Strength - 6,000 lbs.
 - Connectors - Steel ANSI rated locking snap hooks at all three ends
 - Meets OSHA and ANSI Z359.13-2009



Product #: RL-30299(6)
Connex™ 6' Twin Leg "Y" Style 100% Tie Off Internal Shock Absorbing Lanyard with 1 Locking Snap Hook, 2 #18 Locking Rebar Hooks

- Product Information:**
- Length of Lanyard - 6'
 - Rated Internal Shock Absorber Free Fall Limit - 6'
 - Webbing Break Strength - 6,000 lbs.
 - Connectors - Steel ANSI rated locking snap hook at attachment end and one steel ANSI rated rebar hook at anchorage end
 - Meets OSHA and ANSI Z359.13-2009



Product #: RL-30298(12)
Connex™ 6' Twin Leg "Y" Style 100% Tie Off Extended (12') Rated Free fall Internal Shock Absorbing Lanyard With 3 Locking Snap Hooks

- Product Information:**
- Length of Lanyard - 6'
 - Rated Internal Shock Absorber Free Fall Limit - 12'
 - Webbing Break Strength - 6,000 lbs.
 - Connectors - Steel ANSI rated locking snap hooks at all three ends
 - Meets OSHA and ANSI Z359.13-2009

Shock Absorbing Lanyards Selector Guide	RL-3118(6)	RL-3119(6)	RL-30198(6)	RL-30199(6)	RL-30128(6)	RL-30129(6)	RL-30298(6)	RL-30299(6)	RL-30128(12)	RL-30298(12)
Lanyard Length	6'									
Maximum Free Fall	6'	6'	6'	6'	6'	6'	6'	6'	12'	12'
Maximum Arresting Force	900 lbs. Maximum Arresting Force (MAF)								1,350 lbs. MAF	
Anchorage Connections	2 Snap	1 Snap/1 Rebar	3 Snap	1 Snap/2 Rebar	2 Snap	1 Snap/1 Rebar	3 Snap	1 Snap/2 Rebar	2 Snap	3 Snap
Style of Shock Absorber	Clear Pack	Clear Pack	Clear Pack	Clear Pack	Internal	Internal	Internal	Internal	Extended Free Fall	Extended Free Fall
Single or Twin Legged	Single		Twin		Single		Twin		Single	Twin

Product #: RL-3128(12)