

CONNECTORS

Get connected to your fall protection. We offer both steel carabiners and wire anchor forms, depending upon what type of fall protection equipment you use and how you need to connect to the rest of your system. Every Rigid Lifelines® connector meets all ANSI Z359 requirements including 3,600 lbs. rated gates where applicable. There are various connector sizes designed to meet the needs of many types of anchorage points. Each connector is exceptionally lightweight to minimize any potential drag for the user.



Product #: RL-113-A
Small Steel Carabiner - .85" Gate Opening

Product Information:

- Meets ANSI Z359.12-2009
- Minimum Break Strength: 5,000 lbs./23kN
- Gate Strength: 3,600 lbs.
- Material: Alloy Steel
- Gate Opening: .85"
- Finish: Golden Yellow Galvanized
- Net Weight: .62 lbs.
- Proof Load Tested



Product #: RL-134A
Large Steel Carabiner - 2" Gate Opening

Product Information:

- Meets ANSI Z359.12-2009
- Minimum Break Strength: 5,000 lbs./23kN
- Gate Strength: 3,600 lbs.
- Material: Alloy Steel
- Gate Opening: 2"
- Finish: Golden Yellow Galvanized
- Net Weight: 1.89 lbs.
- Proof Load Tested



Products #: RL-141, RL-142, RL-143
Wire Anchor Form Stainless Steel Gate Opening

Product Information:

- Meets ANSI Z359.1-2007
- Minimum Break Strength: 5,000 lbs./23kN
- Heavy Duty SAE 304 Stainless Steel Construction
- #141 Fits rated structural members up to 5" in diameter
- #142 Fits rated structural members up to 4" in diameter
- #143 Fits rated structural members up to 3" in diameter
- Only intended for overhead applications

ROPE GRAB

Get a grip on your rope with a Connex™ Rope Grab. Our rope grab device is designed with a 3-foot shock absorbing lanyard built into it for energy absorption during fall arrest. It also features locking snap hooks for a secure harness attachment. These are lightweight and perfect for use with rope that is 5/8" in diameter.



Product #: RL-3002
Connex Manual Rope Grab with 3' Shock Absorbing Lanyard

Product Information:

- Length of Rope Grab Assembly – 21 3/4"
- Steel Rope Grab for use with suitably rated 5/8" rope lifeline
- Shock Pack with rope grab at one end, other end with locking snap hook for attachment to harness
- Meets requirements of ANSI and OSHA

ANCHOR STRAPS

Anchor straps can be choked around suitably rated I-beams or other suitably rated structures. Typically, vertical lifelines, such as lanyards, SRL's and rope lifelines are connected to the anchor strap's D-Ring.



Product #: RL-AS3
3' Choker Style Cross Arm Anchor Strap with 2.75" Wear Pad

Product Information:

- Length of Anchor Strap - 3'
- Made up of 1.75" wide Polyester webbing stitched with 2.75" webbing wear pad on the back for extra protection
- Anchor Strap having one side with small forged D-Ring, and other side with large forged D-Ring
- PVC rollers where webbing is looped around D-Rings for added protection
- Meets OSHA and ANSI Z359.1