

# Pneumatic Lift Tables

## Pneumatic Scissor Lifts

These units achieve lift via a heavy-duty airbag system. They require no electricity and can be used anywhere that shop air is available. They require less maintenance than conventional scissor lifts and because there is no hydraulic fluid, there is no potential for process contamination.

### Features

- Pressure relief valve standard
- Lifetime warranty on actuator
- Air requirements - 80 psi at 15 cfm
- Standard pedestal control
- Optional foot control
- Designed for stationary use and must be lagged to the floor
- Custom platforms available
- Hand control is not available on any pneumatic lift/tilts

| Model Number       | Load Capacity | Raised Height | Lowered Height | Vertical Travel | Base Size W x L | Platform Size W x L | Shipping Weight |
|--------------------|---------------|---------------|----------------|-----------------|-----------------|---------------------|-----------------|
| <b>AX10 Series</b> |               |               |                |                 |                 |                     |                 |
| AX10-3648          | 1000 lbs      | 29"           | 8"             | 21"             | 36 x 48"        | 36 x 48"            | 820 lbs         |
| AX10-4848          | 1000 lbs      | 29"           | 8"             | 21"             | 36 x 48"        | 48 x 48"            | 890 lbs         |
| AX10-4856          | 1000 lbs      | 29"           | 8"             | 21"             | 36 x 48"        | 48 x 56"            | 935 lbs         |
| AX10-4860          | 1000 lbs      | 29"           | 8"             | 21"             | 36 x 48"        | 48 x 60"            | 960 lbs         |
| <b>AX20 Series</b> |               |               |                |                 |                 |                     |                 |
| AX20-3648          | 2000 lbs      | 32"           | 8"             | 24"             | 36 x 48"        | 36 x 48"            | 855 lbs         |
| AX20-4848          | 2000 lbs      | 32"           | 8"             | 24"             | 36 x 48"        | 48 x 48"            | 915 lbs         |
| AX20-4856          | 2000 lbs      | 32"           | 8"             | 24"             | 36 x 48"        | 48 x 56"            | 955 lbs         |
| AX20-4860          | 2000 lbs      | 32"           | 8"             | 24"             | 36 x 48"        | 48 x 60"            | 1040 lbs        |
| <b>AX40 Series</b> |               |               |                |                 |                 |                     |                 |
| AX40-4848          | 4000 lbs      | 32"           | 8"             | 24"             | 48 x 48"        | 48 x 48"            | 1040 lbs        |
| AX40-4856          | 4000 lbs      | 32"           | 8"             | 24"             | 48 x 48"        | 48 x 56"            | 1115 lbs        |
| AX40-4860          | 4000 lbs      | 32"           | 8"             | 24"             | 48 x 48"        | 48 x 60"            | 1135 lbs        |

## Heavy-Duty Pneumatic Scissor Lifts

These pneumatic scissor lifts feature additional airbags to achieve increased capacity for handling heavier loads up to 8,000 lbs.

### Features

- Lifetime warranty on actuator
- Pressure relief valve standard
- Air requirements are 80 psi at 15 cfm
- Standard pedestal control
- Optional foot control
- Transportable version available
- No floor lagging necessary
- Custom platforms available

| Model Number        | Load Capacity | Raised Height | Lowered Height | Vertical Travel | Base Size W x L | Platform Size W x L | Shipping Weight |
|---------------------|---------------|---------------|----------------|-----------------|-----------------|---------------------|-----------------|
| <b>AXS20 Series</b> |               |               |                |                 |                 |                     |                 |
| AXS20-3648          | 2000 lbs      | 36"           | 12"            | 24"             | 36 x 48"        | 36 x 48"            | 855 lbs         |
| AXS20-4848          | 2000 lbs      | 36"           | 12"            | 24"             | 36 x 48"        | 48 x 48"            | 915 lbs         |
| AXS20-4856          | 2000 lbs      | 36"           | 12"            | 24"             | 36 x 48"        | 48 x 56"            | 955 lbs         |
| AXS20-4860          | 2000 lbs      | 36"           | 12"            | 24"             | 36 x 48"        | 48 x 60"            | 1040 lbs        |
| <b>AXS40 Series</b> |               |               |                |                 |                 |                     |                 |
| AXS40-3648          | 4000 lbs      | 36"           | 12"            | 24"             | 36 x 48"        | 36 x 48"            | 1020 lbs        |
| AXS40-4848          | 4000 lbs      | 36"           | 12"            | 24"             | 36 x 48"        | 48 x 48"            | 1040 lbs        |
| AXS40-4856          | 4000 lbs      | 36"           | 12"            | 24"             | 36 x 48"        | 48 x 56"            | 1115 lbs        |
| AXS40-4860          | 4000 lbs      | 36"           | 12"            | 24"             | 36 x 48"        | 48 x 60"            | 1135 lbs        |
| <b>AXS60 Series</b> |               |               |                |                 |                 |                     |                 |
| AXS60-4848          | 6000 lbs      | 36"           | 12"            | 24"             | 48 x 48"        | 48 x 48"            | 1170 lbs        |
| AXS60-4856          | 6000 lbs      | 36"           | 12"            | 24"             | 48 x 48"        | 48 x 56"            | 1315 lbs        |
| AXS60-4860          | 6000 lbs      | 36"           | 12"            | 24"             | 48 x 48"        | 48 x 60"            | 1335 lbs        |
| <b>AXS80 Series</b> |               |               |                |                 |                 |                     |                 |
| AXS80-4848          | 8000 lbs      | 36"           | 12"            | 24"             | 48 x 48"        | 48 x 48"            | 1340 lbs        |
| AXS80-4856          | 8000 lbs      | 36"           | 12"            | 24"             | 48 x 48"        | 48 x 56"            | 1415 lbs        |
| AXS80-4860          | 8000 lbs      | 36"           | 12"            | 24"             | 48 x 48"        | 48 x 60"            | 1435 lbs        |



Pneumatic options on page 30